

H-CAT30

DIVERTER MODULE - Series 1500

Controls Platform: H-20 Full Control

POWERED BY
TREW

H-CAT30 diverter modules provide a 30° angle to move packages and totes to a separate line. The design allows for the unit to be placed close together to provide sortation-type package flow. It uses MDR technology to drive the rollers, belts and lifting motion. It is fully powered by 24 volt DC electricity, with rates up to 50 products/min. There is no electric actuator or pneumatic cylinder reducing overall project cost and installation effort. Pre-wired for factory testing and quick installation.

Minimum Product Size 7" X 7"
Up to 180 FPM
Gear Ratio 18:1
Up to 75 lbs
O-Band



KEY FEATURES AND BENEFITS

- Rate up to 50 products per min (Conditional on Application)
- Standard to medium weight applications up to 75 lbs
- Resilient and durable construction. Perfect for distribution, warehouse, process lines and postal applications
- Electrical components have quick connect terminals for easy installations and expansion
- Durable, high tension O-bands
- Available ZPA Analyzer allows for system diagnostic and commissioning
- IP54 Standard, Up to IP67
- Positive Drive, O-Band
- Programming Required

HCAT30

DIVERTER MODULE - Series 1500

SERIES 1500, STANDARD GOODS, FULL, ZPA, FULL, 24 V DC 30IN ZONE 30 DEG POP-UP DIVERT HCAT30 90IN L

Description

90IN HCAT30, 30DEG DIVERT TO RIGHT, SERIES 1500, 30IN ZONE, 15IN BF, RSL 7.5IN, LH FULL CONTROL

90IN HCAT30, 30DEG DIVERT TO LEFT, SERIES 1500, 30IN ZONE, 15IN BF, RSL 7.5IN, RH FULL CONTROL

90IN HCAT30, 30DEG DIVERT TO RIGHT, SERIES 1500, 30IN ZONE, 21IN BF, RSL 7.5IN, LH FULL CONTROL

90IN HCAT30, 30DEG DIVERT TO LEFT, SERIES 1500, 30IN ZONE, 21IN BF, RSL 7.5IN, RH FULL CONTROL

SERIES 1500, STANDARD GOODS, FULL, ZPA, FULL, 24 V DC 30IN ZONE 30 DEG POP-UP DIVERT HCAT30 120IN L

Description

120IN HCAT30, 30DEG DIVERT TO RIGHT, SERIES 1500, 30IN ZONE, 27IN BF, RSL 7.5IN, LH FULL CONTROL

120IN HCAT30, 30DEG DIVERT TO LEFT, SERIES 1500, 30IN ZONE, 27IN BF, RSL 7.5IN, RH FULL CONTROL

120IN HCAT30, 30DEG DIVERT TO RIGHT, SERIES 1500, 30IN ZONE, 33IN BF, RSL 7.5IN, LH FULL CONTROL

120IN HCAT30, 30DEG DIVERT TO LEFT, SERIES 1500, 30IN ZONE, 33IN BF, RSL 7.5IN, RH FULL CONTROL

120IN HCAT30, 30DEG DIVERT TO RIGHT, SERIES 1500, 30IN ZONE, 36IN BF, RSL 7.5IN, LH FULL CONTROL

120IN HCAT30, 30DEG DIVERT TO LEFT, SERIES 1500, 30IN ZONE, 36IN BF, RSL 7.5IN, RH FULL CONTROL